



jQuery Mobile

References

Collectors: **MohaMad Fathi**
Adviser: **Engineer Abas Baghery Yazdi**
www.MiMFa.net

Content

ELEMENTS REFERENCE	8
BUTTON	9
CHECKBOX	10
COLLAPSIBLE	11
COLLAPSIBLE SET	13
CONTENT	14
CONTROLGROUP	15
DIALOG	16
ENHANCEMENT	17
FIELD CONTAINER	18
FIXED TOOLBAR	19
FLIP TOGGLE SWITCH	20

FOOTER	21
HEADER	22
LINK	23
LISTVIEW	24
LISTVIEW ITEM	25
NAVBAR	26
PAGE	27
POPUP	28
RADIO BUTTON	30
SELECTMENU	31
SELECT	32
SLIDER	33
TEXT INPUT & TEXTAREA	34
TOOLBAR	35
<u>ATTRIBUTE REFERENCE</u>	<u>36</u>

CLASS="VALUE"	37
DATA-ROLE="VALUE"	40
DATA-REL="VALUE"	42
DATA-TYPE="VALUE"	42
DATA-FILTER="VALUE"	43
DATA-DIALOG="VALUE"	43
DATA- FULLSCREEN="VALUE"	44
DATA- INSET="VALUE"	44
DATA-AUTODIVIDERS="VALUE"	45
DATA-DISMISSIBLE ="VALUE"	45
DATA-SWIPE-CLOSE="VALUE"	46
DATA-COLLAPSED="VALUE"	46
DATA-CLEAR-BTN="VALUE"	47
DATA-CORNERS="VALUE"	47
DATA-NATIVE-MENU="VALUE"	48
DATA-SHOW-VALUE="VALUE"	48

DATA-POPUP-ENABLED="VALUE"	49
DATA-HIGHLIGHT="VALUE"	49
DATA-TRANSITION="VALUE"	50
DATA-DIRECTION="VALUE"	51
DATA-POSITION-FIXED ="VALUE"	51
DATA-POSITION ="VALUE"	52
DATA-POSITION-TO ="VALUE"	53
DATA-ARROW ="VALUE"	53
DATA-ICONPOS ="VALUE"	54
DATA-THEME="VALUE"	54
DATA-OVERLAY-THEME="VALUE"	55
DATA-DISPLAY="VALUE"	55
DATA-ICON="VALUE"	56
DATA-MODE="VALUE"	59
DATA-INPUT="VALUE"	59
DATA-PRIORITY="VALUE"	59

DATA-COLUMN-BTN-TEXT="VALUE"	60
PLACEHOLDER="VALUE"	60
DATA-FILTERTEXT="VALUE"	60
DATA-ON-TEXT="VALUE"	61
DATA-OFF-TEXT="VALUE"	61

Elements reference

The jQuery Mobile framework uses HTML5 **data-** attributes to allow for markup-based initialization and configuration of widgets. These attributes are completely optional; calling plugins manually and passing options directly is also supported. To avoid naming conflicts with other plugins or frameworks that also use **data-**attributes, set a custom namespace by modifying the **ns global option**.

Button

Links with **data-role="button"**. Input-based buttons, links in toolbars, and button elements are auto-enhanced, no **data-role** required.

data-corners	true false
data-icon	home delete plus arrow-u arrow-d check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search
data-iconpos	left right top bottom notext
data-iconshadow	true false
data-inline	true false
data-mini	true false - Compact sized version
data-shadow	true false
data-theme	swatch letter (a-z)

Multiple buttons can be wrapped in a container with a **data-role="controlgroup"** attribute for a vertically grouped set. Add the **data-type="horizontal"** attribute for the buttons to sit side-by-side. Add the **data-mini="true"** to get the mini/compact sized version for all the buttons that appear in the controlgroup.

Checkbox

Pairs of labels and inputs with **type="checkbox"** are auto-enhanced, no **data-role** required

data-mini	true false - Compact sized version
data-role	none (prevents auto-enhancement to use native control)
data-theme	swatch letter (a-z) - Added to the form element

Multiple checkboxes can be wrapped in a container with a **data-role="controlgroup"** attribute for a vertically grouped set. Add the **data-type="horizontal"** attribute for the checkboxes to sit side-by-side. Add the **data-mini="true"** to get the mini/compact sized version for all the checkboxes that appear in the controlgroup.

Collapsible

A heading and content wrapped in a container with the **data-role="collapsible"**

data-collapsed	true false
data-collapse-cue-text	string - Text used to provide audible feedback for users with screen reader software. Default: " click to collapse contents"
data-collapsed-icon	home delete plus arrow-u arrow-d carat-l carat-t carat-r carat-b check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search false
data-content-theme	swatch letter (a-z)
data-expand-cue-text	string - Text used to provide audible feedback for users with screen reader software. Default: " click to expand contents"
data-expanded-icon	home delete plus arrow-u arrow-d carat-l carat-t carat-r carat-b check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search
data-iconpos	left right top bottom
data-inset	true false
data-mini	true false - Compact sized version
data-theme	swatch letter (a-z)

data-collapsed	true false
data-content-theme	swatch letter (a-z)
data-iconpos	left right top bottom
data-mini	true false - Compact sized version
data-theme	swatch letter (a-z)

Collapsible set

A number of collapsibles wrapped in a container with the **data-role="collapsible-set"**

data-collapsed-icon	home delete plus arrow-u arrow-d carat-l carat-t carat-r carat-b check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search
data-content-theme	swatch letter (a-z) - Sets all collapsibles in set
data-expanded-icon	home delete plus arrow-u arrow-d carat-l carat-t carat-r carat-b check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search
data-iconpos	left right top bottom notext
data-inset	true false
data-mini	true false - Compact sized version
data-theme	swatch letter (a-z) - Sets all collapsibles in set
data-content-theme	swatch letter (a-z) - Sets all collapsibles in set
data-iconpos	left right top bottom notext
data-mini	true false - Compact sized version
data-theme	swatch letter (a-z) - Sets all collapsibles in set

Content

Container with data-role="content"

data-theme

swatch letter (a-z)

Controlgroup

DIV or FIELDSET container with **data-role="controlgroup"**. Visually integrate multiple button-styled inputs of a single type (**checkboxes, link-based buttons, radio buttons, selects**) into a group. For grouping form checkboxes and radio buttons, the **fieldset** container is recommended inside a div container with the **data-role="fieldcontain"**, to improve label styling.

data-exclude-invisible	true false - Sets whether to exclude invisible children in the assignment of rounded corners
data-mini	true false - Compact sized version for all items in the controlgroup
data-theme	swatch letter (a-z)
data-type	horizontal vertical - For horizontal or vertical item alignment
data-mini	true false - Compact sized version for all items in the controlgroup
data-type	horizontal vertical - For horizontal or vertical item alignment

Dialog

Container with **data-role="dialog"** or linked to with **data-rel="dialog"** on the anchor.

data-close-btn-text	string (text for the close button, dialog only)
data-dom-cache	true false
data-overlay-theme	swatch letter (a-z) - overlay theme when the page is opened in a dialog
data-theme	swatch letter (a-z)
data-title	string (title used when page is shown)

Enhancement

Container with `data-enhance="false"` or `data-ajax="false"`

data-enhance	true false
data-ajax	true false

Any DOM elements inside a **data-enhance="false"** container, save for **data-role="page | dialog"** elements, will be ignored during initial enhancement and subsequent **create** events provided that the **\$.mobile.ignoreContentEnabled** flag is set prior to the enhancement (eg in a **mobileinit** binding).

Any link or form element inside **data-ajax="false"** containers will be ignored by the framework's navigation functionality when **\$.mobile.ignoreContentEnabled** is set to true.

Field container

Container with **data-role="fieldcontain"** wrapped around label/form element pair

Note: data-role="fieldcontain" is deprecated as of jQuery Mobile 1.4.0 and will be removed in 1.5.0. Add class ui-field-contain instead.

Fixed Toolbar

Container with data-role="header" or data-role="footer" plus the attribute data-position="fixed"

data-disable-page-zoom	true false - User-scaling-ability for pages with fixed toolbars
data-fullscreen	true false - Setting toolbars over the page-content
data-tap-toggle	true false - Ability to toggle toolbar-visibility on user tap/click
data-transition	slide fade none - Show/hide-transition when a tap/click occurs
data-update-page-padding	true false - Have the page top/bottom padding updated on other events than when page is shown as well (resize, transition, "updateLayout")
data-visible-on-page-show	true false - Toolbar-visibility when parent page is shown

Flip toggle switch

Select with **data-role="slider"**, two options only

data-mini	true false - Compact sized version
data-role	none (prevents auto-enhancement to use native control)
data-theme	swatch letter (a-z) - Added to the form element
data-track-theme	swatch letter (a-z) - Added to the form element

Footer

Container with data-role="footer"

data-id	string (unique id, useful in persistent footers)
data-position	fixed
data-fullscreen	true (used in conjunction with fixed toolbars)
data-theme	swatch letter (a-z)

Header

Container with data-role="header"

data-id	string (unique id, useful in persistent headers)
data-position	fixed
data-fullscreen	true (used in conjunction with fixed toolbars)
data-theme	swatch letter (a-z)

Link

Links, including those with a **data-role="button"**, and form submit buttons share these attributes

data-ajax	true false
data-direction	reverse (reverse page transition animation)
data-dom-cache	true false
data-prefetch	true false
data-rel	back (to move one step back in history) dialog (to open link styled as dialog, not tracked in history) external (for linking to another domain)
data-transition	fade flip flow pop slide slidedown slidefade slideup turn none

Listview

OL or UL with data-role="listview"

data-count-theme	swatch letter (a-z) (default "c" if unset)
data-divider-theme	swatch letter (a-z) (default "b" if unset)
data-filter	true false
data-filter-placeholder	string
data-filter-theme	swatch letter (a-z)
data-header-theme	swatch letter (a-z)
data-inset	true false
data-split-icon	home delete plus arrow-u arrow-d check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search
data-split-theme	swatch letter (a-z) (default "b" if unset)
data-theme	swatch letter (a-z)

Listview item

LI within a listview

data-filtertext	string (filter by this value instead of inner text)
data-icon	home delete plus arrow-u arrow-d check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search false
data-role	list-divider
data-theme	swatch letter (a-z) - can also be set on individual LIs

The **data-icon** attribute is only applicable for a listview item, if it contains a link.

Navbar

A number of LIs wrapped in a container with **data-role="navbar"**

data-iconpos left | right | top | bottom | notext

To add icons to the navbar items, the **data-icon** attribute is used, specifying a standard mobile icon for each item.

Navbars inherit the theme-swatch from their parent container. Setting the **data-theme** attribute to a navbar is not supported. The **data-theme** attribute can be set individually to the links inside a navbar.

Page

Container with data-role="page"

data-add-back-btn	true false (auto add back button, header only)
data-back-btn-text	string
data-back-btn-theme	swatch letter (a-z)
data-close-btn-text	string (text for the close button, dialog only)
data-dom-cache	true false
data-fullscreen	true (used in conjunction with fixed toolbars) Deprecated in 1.1 - use on header and footer instead.
data-overlay-theme	swatch letter (a-z) - overlay theme when the page is opened in a dialog
data-theme	swatch letter (a-z)
data-title	string (title used when page is shown)
data-url	url (value for updating the URL, instead of the url used to request the page)

Popup

Container with data-role="popup"

data-corners	true false
data-dismissible	true false - If set to false prevents popup closing by clicking outside of the popup or pressing the Escape key
data-history	true false - Sets whether the popup creates a browser history item when it opens. If set to false, it will not create a history item, and will thus not be closeable via the browser's "Back" button.
data-overlay-theme	swatch letter (a-z) - Default "null" (transparent background)
data-position-to	origin window selector - "origin" indicates that the popup is to be centered over the link that opens it. "window" indicates that it is to be centered in the browser window. If you give a jQuery selector, it will be centered over the first element returned by the selector, if that element is visible. Otherwise, it will be centered in the browser window.
data-shadow	true false
data-theme	swatch letter (a-z) none - Default inherited, "none" sets the popup to transparent
data-tolerance	30,15,30,15 - Distance from the edges of the window (top, right, bottom, left)

data-transition	none transition - The transition to use when making the popup appear/disappear.
Anchor with a <code>data-rel="popup"</code> opens the popup	
data-position-to	origin - Centers the popup over the link that opens it jQuery selector - Centers the popup over the specified element window - Centers the popup in the window
data-rel	popup - For opening a popup
data-transition	fade flip flow pop slide slidedown slidefade slideup turn none - The transition to be used when showing/hiding the popup

Radio button

Pairs of labels and inputs with **type="radio"** are auto-enhanced, no **data-role** required

data-mini	true false - Compact sized version
data-role	none (prevents auto-enhancement to use native control)
data-theme	swatch letter (a-z) - Added to the form element

Multiple radio buttons can be wrapped in a container with a `data-role="controlgroup"` attribute for a vertically grouped set. Add the `data-type="horizontal"` attribute for the radio buttons to sit side-by-side. Add the `data-mini="true"` to get the mini/compact sized version for all the radio buttons that appear in the controlgroup.

Selectmenu

All `select` form elements are auto-enhanced, no `data-role` required

data-divider-theme	swatch letter (a-z) - Default "b" - Only applicable if <code>optgroup</code> support is used in non-native selects
data-icon	home delete plus arrow-u arrow-d carat-l carat-t carat-r carat-b check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search false
data-iconpos	left right top bottom notext
data-inline	true false
data-mini	true false - Compact sized version
data-native-menu	true false
data-overlay-theme	swatch letter (a-z) - Overlay theme for non-native selects
data-placeholder	true false - Can be set on <code>option</code> element of a non-native select
data-role	none - Prevents auto-enhancement to use native control
data-theme	swatch letter (a-z) - Added to the form element

Select

All **select** form elements are auto-enhanced, no **data-role** required

data-icon	home delete plus arrow-u arrow-d check gear grid star custom arrow-r arrow-l minus refresh forward back alert info search
data-iconpos	left right top bottom notext
data-inline	true false
data-mini	true false - Compact sized version
data-native-menu	true false
data-overlay-theme	swatch letter (a-z) - overlay theme for non-native selects
data-placeholder	true false - Add to the Option
data-role	none (prevents auto-enhancement to use native control)
data-theme	swatch letter (a-z) - Added to the form element

Multiple selects can be wrapped in a fieldset with a **data-role="controlgroup"** attribute for a vertically grouped set. Add the **data-type="horizontal"** attribute for the selects to sit side-by-side.

Slider

Inputs with **type="range"** are auto-enhanced, no **data-role** required

data-highlight	true false - Adds an active state fill on track to handle
data-mini	true false - Compact sized version
data-role	none (prevents auto-enhancement to use native control)
data-theme	swatch letter (a-z) - Added to the form element
data-track-theme	swatch letter (a-z) - Added to the form element

Text input & Textarea

Input `type="text|number|search|etc."` or `textarea` elements are auto-enhanced, no `data-role` required

data-clear-btn	true false - Adds a clear button
data-clear-btn-text	string - Text for the close button. Default: "clear text"
data-mini	true false - Compact sized version
data-role	none - Prevents auto-enhancement to use native control
data-theme	swatch letter (a-z) - Added to the form element

Toolbar

Container with data-role="header" or data-role="footer"

data-add-back-btn	true false - Auto add back button, header only
data-back-btn-text	string - Header only
data-back-btn-theme	swatch letter (a-z) - Header only
data-id	string - Unique ID. Required for persistent footers
data-position	fixed
data-theme	swatch letter (a-z)

Attribute reference

JQuery Mobile attribute and classes and values tables...

class="Value"

Value	Action
ui-content	class adds extra padding and margin inside the page content
ui-responsive	Responsive design.
ui-filterable	Filterable Elements
ui-btn	making them attractive and useable on both mobile devices and desktop computers.
ui-btn-active	To achieve this look without having to tap the link
ui-state-persist	look for each button that represents the page the user is on.
ui-btn-inline	buttons take up the full width of the screen
ui-btn-b	Changes the color of the button to a black background with white text (default is gray background with black text).
ui-corner-all	Adds rounded corners to the button
ui-mini	Makes the button smaller
ui-shadow	Adds shadows to the button
ui-nodisc-icon	By default, all icons have a gray circle (disc) around them. To remove the circle, add this class to the element or its container
ui-btn-icon-notext	To only display the icon

ui-alt-icon	By default, all icons are white. To change the icon color to black, add this class to the element or its container:
ui-btn-icon-left	Icon to left position
ui-btn-icon-right	Icon to right position
ui-btn-icon-top	Icon to top position
ui-btn-icon-bottom	Icon to bottom position
ui-icon-arrow-l	Left Arrow Icon
ui-icon-arrow-r	Right Arrow Icon
ui-icon-info	Information Icon
ui-icon-delete	Delete Icon
ui-icon-back	Back Icon
ui-icon-audio	Speakers Icon
ui-icon-lock	Padlock Icon
ui-icon-search	Search Icon
ui-icon-alert	Alert Icon
ui-icon-grid	Grid Icon
ui-icon-home	Home Icon
ui-li-icon	To add a standard 16x16px icon to your list, add an <code></code> element
ui-li-count	To add count bubbles, use an inline element, such as <code></code>

ui-grid-solo	100% ui-block-a
ui-grid-a	50% / 50% ui-block-a b
ui-grid-b	33% / 33% / 33% ui-block-a b c
ui-grid-c	25% / 25% / 25% / 25% ui-block-a b c d
ui-grid-d	20% / 20% / 20% / 20% / 20% ui-block-a b c d e
ui-hidden-accessible	To hide the object
ui-field-contain	To make labels and form elements look properly on wider screens

data-role="Value"

Value	Action
page	is the page displayed in the browser
header	creates a toolbar at the top of the page (often used for title or search
main	defines the content of the page, like text, images, buttons, forms, etc.
footer	creates a toolbar at the bottom of the page
table	Create a table.
listview	To create a list with make the items tappable, specify a link inside each list item ()
list-divider	To specify a list divider
popup	The content inside this <div> is the actual content that will pop up.
panel	Panels in jQuery Mobile will slide out from the left or the right side of the screen with additional content.
controlgroup	specify whether to group object horizontally or vertically (with data-type)
navbar	The bar is coded as an unordered list of links wrapped inside a <div> element
collapsible	allow you to hide or show content, which is useful for storing parts of information.
collapsibleset	Collapsible sets are collapsible blocks that are grouped together (often referred to as an accordion). When a new block is opened, all other blocks close.
flipswitch	To create a flip switch, use <input type="checkbox">

none	To prevent jQuery Mobile to automatically style tappable/clickable elements
-------------	---

data-rel="Value"

Value	Action
back	To create a Back button. (exist value in href is not important)
close	You can also close the panel by using a button.
popup	Open the popup page with clicked on this link.

data-type="Value"

Value	Action
horizontal	horizontally organization
vertical	vertically organization
search	Create an <input> element with a specified id and add the data-type="search" attribute

data-filter="Value"

Value	Action
true	The element you want to be filterable
false	The element you want to be not filterable

data-dialog="Value"

Value	Action
true	to the page you want displayed as a dialog.
false	to the page you want no displayed as a dialog.

data- fullscreen="Value"

Value	Action
true	fullscreen positions.
false	not fullscreen positions.

data- inset="Value"

Value	Action
true	To style your lists with rounded corners and some margin
false	To style your lists without rounded corners and some margin

data-autodividers="Value"

Value	Action
true	creates dividers with uppercased first letters of the item's text.
false	Do not creates dividers with uppercased first letters of the item's text.

data-dismissible ="Value"

Value	Action
true	Specifies whether the panel can be closed by clicking outside of it.
false	Specifies whether the panel can not be closed by clicking outside of it.

data-swipe-close="Value"

Value	Action
true	Specifies whether the panel can be closed by swiping.
false	Specifies whether the panel can not be closed by swiping.

data-collapsed="Value"

Value	Action
true	Collapsed content.
false	No collapsed content.

data-clear-btn="Value"

Value	Action
true	Clear all objects value in forms.
false	Do not clear all objects value in forms.

data-corners="Value"

Value	Action
true	shows how mobile platforms have their own way of showing a select menu.
false	Specifies whether the button should not have rounded corners

data-native-menu="Value"

Value	Action
true	Specifies whether the button should have rounded corners
false	display the same on all mobile devices, use jQuery's own custom select menu

data-show-value="Value"

Value	Action
true	To show the value on the slider button
false	To not show the value on the slider button

data-popup-enabled="Value"

Value	Action
true	to the value to pop up on your screen like a tooltip (as you slide)
false	to the value to not pop up on your screen like a tooltip (as you slide)

data-highlight="Value"

Value	Action
true	to highlight the track up to the slider value
false	To not highlight the track up to the slider value

data-transition="Value"

Value	Action
fade	Fades to the next page
flip	Flips to the next page from back to front
flow	Throws the current page away and comes in with the next page
pop	Goes to the next page like a popup window
slide	Slides to the next page from right to left
slidefade	Slides from right to left and fades in the next page
slideup	Slides to the next page from bottom to top
slidedown	Slides to the next page from top to bottom
turn	Turns to the next page
none	No transition effect

data-direction="Value"

Value	Action
reverse	All effects above also support reverse/backward actions

data-position-fixed = "Value"

Value	Action
true	Disabled scrolling with content scroll. (e.g. for panel)
false	Enabled scrolling with content scroll. (e.g. for panel)

data-position = "Value"

Value	Action
inline	Objects (e.g. Headers and footers) are inline with the page content
fixed	Objects will remain positioned at the top and bottom of the page
fullscreen	Behaves like fixed; Objects (e.g. Headers and footers) will remain positioned at the top and bottom, but also over the page content. It is also slightly see-through
left	left alignment (e.g. for panel positions)
right	right alignment(e.g. for panel positions)
top	top alignment(e.g. for panel positions)
bottom	bottom alignment(e.g. for panel positions)

data-position-to = "Value"

Value	Action
window	Objects (e.g Popup) will appear centered within the window
#myId	Objects (e.g Popup) is positioned over the element with a specified #id
origin	Objects (e.g Popup) is positioned directly over the clicked element

data-arrow = "Value"

Value	Action
l	To add an arrow to the popup's border in left
r	To add an arrow to the popup's border in right
t	To add an arrow to the popup's border in top
b	To add an arrow to the popup's border in bottom

data-iconpos = "Value"

Value	Action
left	left icon alignment
right	right icon alignment
top	top icon alignment
bottom	bottom icon alignment

data-theme="Value"

Value	Action
a	add a light theme
b	add a dark theme

data-overlay-theme="Value"

Value	Action
a	add a light overlay
b	add a dark overlay

data-display="Value"

Value	Action
overlay	Displays the panel over the content
push	Animates both the panel and the page at the same time
reveal	The panel will sit under the page and reveal as the page slides away

data-icon="Value"

Value	Action
action	Action (arrow pointing clockwise out of a box)
alert	Alert
audio	Audio / Sound / Speakers
arrow-d-l	Arrow pointing downwards to the left
arrow-d-r	Arrow pointing downwards to the right
arrow-u-l	Arrow pointing upwards to the left
arrow-u-r	Arrow pointing upwards to the right
arrow-l	Arrow pointing left
arrow-r	Arrow pointing right
arrow-u	Arrow pointing up
arrow-d	Arrow pointing down
back	Back (curved arrow pointing counterclockwise upwards)
bars	Bars (three horizontal bars over each other)
bullets	Bullets (three horizontal bullets over each other)
calendar	Calendar

camera	Camera
carat-d	Carat pointing down
carat-l	Carat pointing left
carat-r	Carat pointing right
carat-u	Carat pointing up
check	Checkmark
clock	Clock
cloud	Cloud
comment	Comment
delete	Delete (X)
edit	Edit / Pencil
eye	Eye
forbidden	Forbidden sign
forward	Forward
gear	Gear
grid	Grid
heart	Heart / Love symbol
home	Home

info	Information
location	Location / GPS
lock	Lock / Padlock
mail	Mail / Letter
minus	Minus
navigation	Navigation
phone	Telephone
power	Power (On/off)
plus	Plus
recycle	Recycle
refresh	Refresh
search	Search
shop	Shop / Pag / Purse
star	Star
tag	Tag
user	User / Person
video	Video Camera

data-mode="Value"

Value	Action
columntoggle	will hide columns when there is not enough width to display the data.x

data-input="Value"

Value	Action
#inputid	Its value must match the id of the <input> element.

data-priority="Value"

Value	Action
#	Priority of objects

data-column-btn-text="Value"

Value	Action
text	To change the toggle table button text, use the data-column-btn-text attribute:

placeholder="Value"

Value	Action
text	a short hint that describes the expected value of the input field

data-filtertext="Value"

Value	Action
text	if you want to filter the search to a custom filter text instead

data-on-text="Value"

Value	Action
text	By default, the text on the flip switch is "On" Use this-attributes to change this

data-off-text="Value"

Value	Action
text	By default, the text on the flip switch is "Off" Use this-attributes to change this